

Stormwater Pollution Prevention Program Requirements for Construction

- Contractors must appoint a Stormwater Pollution Prevention Manager.
 - Stormwater Pollution Prevention Manager must perform daily inspections and, when necessary, correct areas of concern.
- All vehicles must enter and exit the construction site at designated locations.
 - 30-50' of stone shall be placed at entrance of construction site to reduce debris on street.



- Construction equipment must be kept away from stormwater barriers, silt fences, fiber rolls, etc.



- Construction equipment must be kept away from designated protection areas, such as stream banks, trees and shrubs, slopes and banks.
 - Post signs and protect these areas with fences.
- Construction vehicles, including concrete trucks, can only be cleaned in designated "WASHOUT AREAS"
 - Wash water can not leave the construction site.
 - Only water can be utilized for vehicle cleaning. Soaps and other detergents are not permitted.
- Stormwater Pollution Protection materials must be maintained.
 - Silt fences and hay bales must be kept in good condition and not permitted to fail or move.
- Buildings can only be washed with water.
 - If cleaners, including acids, or detergents are to be utilized, contact Environmental Health and Safety to establish appropriate containment or disposal requirements.
- Keep equipment off mulched, seeded, or stabilized areas.
 - Post signs indicating this requirement.

